

# Abbreviations

Abbreviation	Description
161	Standard Lockset Prep. = 2 1/8" Dia. Hole in face of door
86	Mortise Lock Edge Prep 8"
AS	Stick Material Series
ASA	Standard 4 7/8" Strike Prep
CL	Centerline
CVR	Concealed Vertical Rod
D/LOCK	Dead Lock Prep on Door
DBL	Double frame and head undersized 1/8"
DE	Double Egress
DW	Drywall returns
EMA	Existing Masonry Anchor (Butterfly type)
F/BOLT	Flush Bolt Reinforcement
G90	Hot Dip Galvanized (1/25 oz/ft2) ZF275
GA	Gauge
HCC	Honeycomb Core – default if not specified
HS	Steel Stiffened Series Doors – Fibreglass default core if not specified
HWT	Heavy Weight Hinge Reinforcing
INS	Polystyrene Core
JD	Jamb Depth
KD	Knock Down
LABEL	Fire Rated openings
LBR	Less Bottom Rod for concealed vertical rod
LHR	Left Hand Reverse
LS	Lock Seam Edge
P/A	Parallel Arm Closer Reinforcing – labelled frames
PO	Your Purchase Order number
REG	Regular Arm Closer Reinforcing – labelled frames
REV	Reversible Swing (Closer Reinf. Top & Bottom)
RHR	Right Hand Reverse
RP	Rim Exit Device Reinforcing
SSF	Steel Stiffened + Fibreglass
STC	Acoustical Assemblies
STYRENE	Polystyrene R6.5
SUA	Welded Frame
THT	Throat of Frame
URETHANE	Polyisocyanurate R11.1
WO	Our Work Order number
WS	Weld Seam Door with Interlocking Ribs & Fibreglass Core